




WASHERS

Nylon IP



High quality Nylon washers designed to maintain ingress protection ratings at the entry into enclosures. Designed for use with cable gland entries, and also suitable for use with stopping plugs, adaptors and other accessories.

Suitable for maintaining ingress protection requirements as specified in IEC/EN 60079

Features

- Suitable for use on hazardous area cable gland entry threads.
- To maintain ingress protection rating of the enclosure.
- Retaining pips make washer captive on metric cable gland entry thread (M20-M75).
- Sealing washer for other thread sizes available on request.

Technical Data

Ingress Protection	Tested to meet IP66, IP67, IP68 and IP69 to IEC/EN 60529
Operating Temperature	-60°C to +130°C
Washer Material	Nylon 66
Washer Thickness	1.5mm

Metric Selection Table

Thread Size	Outside Diameter
M16	24
M20	30
M25	36
M32	46
M40	55
M50	65
M63	80
M75	89
M80	95
M90	106
M100	126

NPT Selection Table

Thread Size	Outside Diameter
½"	28
¾"	35
1"	42
1 ¼"	53
1 ½"	59
2"	70
2 ½"	84
3"	115
3 ½"	126
4"	141

Ordering Example:

Product	Thread Size
Nylon Washer	M25

All dimensions are in millimetres except where * denotes dimensions in inches.