



GU10 Compact Fire Rated Downlights

make smart with



See pg.256-258 for compatibility table

Pressed steel body with aluminium bezel

EN-FD101 - Fixed

EN-FD102 - Adjustable up to 28°

EN-FD103 - Fixed IP65 rated

Loop in / loop out terminal block for quick and easy installation

Tested in 30, 60 and 90 minute solid timber joist fire rated ceilings*

Smart
Lamp options
See pg.27



Standard
Lamp options
See pg.113



See luminaire lamp compatibility on pg.259



Fixed



Adjustable



Fixed IP65



AIR leakage
(excluding
FD101 & FD102)

Cat. No. Input Horz. Adj. Cutout (Ø)

Fixed

EN-FD101W	240V	-	75mm
EN-FD101PC	240V	-	75mm
EN-FD101SN	240V	-	75mm

Adjustable

EN-FD102W	240V	28°	90mm
EN-FD102PC	240V	28°	90mm
EN-FD102SN	240V	28°	90mm

IP65

EN-FD103W	240V	-	75mm
EN-FD103PC	240V	-	75mm
EN-FD103SN	240V	-	75mm

Suffix **W**, **PC** or **SN** for White, Polished Chrome or Satin Nickel finishes.

Lamp not included

*Suitable for use in 30 minute i-joint fire rated ceilings. See pg.262



3 Year Warranty

White, Polished Chrome
& Satin Nickel bezel
finish options

make smart with



works with

.light



Smart
Tuneable GU10
See pg.27

.control



Dimmable
Standard GU10
PLUS



Triac In-line Dimmer
See pg.41




OR
Smart Rotary Dimmer
See pg.35



Non-Dimmable
Standard GU10
PLUS



On/Off Relay
See pg.47



EN-FD101

(H) 125mm Height
(OD) 87mm Overall (Ø)

EN-FD102

(H) 130mm Height
(OD) 100mm Overall (Ø)

EN-FD103

(H) 130mm Height
(OD) 86mm Overall (Ø)