



**GMC**

Gland Mounted Clamp For Hawke Cable Glands



The Hawke GMC is a retro fittable clamp intended for use where additional cable support is required.

**Features**

- Provides additional cable support and pullout resistance
- 3-Part design allows clamp to be retrospectively fitted
- Captive fittings for easy installation
- Manufactured in 316 Stainless Steel
- Offers clamping solution in accordance with BS EN 60079-14 10.3
- Suitable for all styles of Hawke cable gland listed below

**Clamp Selection Table**

Clamp Size	Gland Type	501/321					All Other Glands				
		Os	O	A	B	C	Os	O	A	B	C*
Size 1											
Size 2											
Size 3											
Size 4											
Size 5											

\* Max cable diameter 27.5mm

**Suitable Hawke Cable Glands**

501/321, 501/421, 501/423, 501/453/RAC, 501/453/UNIV, ICG653/UNIV, PSG553/RAC  
 501/453/RAC/L, ICG653/UNIV/L, 121, 123, 151/RAC, 153/RAC, 153/UNIV, 153/RAC/L  
 653/UNIV, 453/RAC, 453/UNIV

**Ordering Example:**

Gland Mounted Clamp / Size 1

**Installation Steps**

- 1 Unscrew tail nut and slide down the cable.
- 2 Choose correct mounting ring from two options supplied and drop onto cable.
- 3 Slide mounting ring onto the gland and re-install the backnut. The clamp mounting ring should now be retained on the gland.
- 4 Hook the clamp arms onto the clamp mounting ring.
- 5 Rotate the clamp arms 90 degrees and pre-engage the screws. Do not yet tighten.
- 6 Whilst the clamp is still loose, pull it in the direction shown to ensure it is up against the backnut.
- 7 Tighten the screws. It is recommended to incrementally tighten each screw to ensure the clamp is tightened equally on both sides.

