

## List No. SB638

### APPLEBY SERVICE ITEMS

Dual Accessory (Single Gang + Double Gang) Dry Lining  
Installation Box with Adjustable Lugs 35mm



- Made from flame retardant thermoplastic
- Tough yellow nylon lugs have large bearing faces for superior strength
- Large flange around the front matches profile of accessory front plates and prevents slipping into the cavity
- 25mm base knockout plus 2 side cable entry points.
- Appropriate for fitting board thicknesses from 6.35-15mm

| Product Specification Data      |                                      | Revision Date: 15/10/2021 |
|---------------------------------|--------------------------------------|---------------------------|
| CE Conformity                   | Yes                                  |                           |
| UKCA Conformity                 | Yes                                  |                           |
| Mounting method                 | Flush mounted (plaster)              |                           |
| Shape                           | Rectangular                          |                           |
| Construction type               | Device connection box (round/square) |                           |
| Model                           | Double                               |                           |
| Length                          | 218 mm                               |                           |
| Width                           | 83 mm                                |                           |
| Depth                           | 36 mm                                |                           |
| Internal depth                  | 35 mm                                |                           |
| For number of electric fittings | 2                                    |                           |
| Mounting switching equipment    | Screwing                             |                           |
| With screws                     | No                                   |                           |
| Material                        | Plastic                              |                           |
| Halogen free                    | No                                   |                           |
| Surface protection              | Untreated                            |                           |
| Colour                          | White                                |                           |
| Degree of protection (IP)       | Other                                |                           |
| Cover model                     | Other                                |                           |
| Cover attachment                | Screwed                              |                           |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.