



13A Socket Outlets

Description

The elegantly styled Slimline Décor range is available in Chrome and Stainless Steel finishes, with either white or black insert colours.

Each product is supplied in its own polybag, protecting it up to the point of installation

Features

- Black or white inserts available
- Metal capped rockers
- Gasket pre-fitted to the accessory to prevent tarnishing
- Protective film on front plate prevents damage during installation
- Captive and backed out terminals
- Terminals have clearly embossed and white printed markings
- Clear white terminal markings
- Only one size 4mm screwdriver needed
- Terminals have large lead-ins
- Recessed earth bar
- Most products have angled terminals to aid installation
- 2 earth terminals on 2 gang sockets
- 25-year guarantee

Range

Double Pole - 13Amp

1 gang DP switched	SD1207
2 gang DP switched	SD1209

Suffix finish with:-

Chrome	CH
Stainless Steel	SS
White or Black inserts	W or B

Longer Length Fixing Screw

50mm Length (Pack	of 10) - Chrome	SP0001CH
50mm Length (Pack	of 10) – Stainless Steel	SP0001SS

75mm Length (Pack of 10) - Chrome	SP0003CH
75mm Length (Pack of 10) – Stainless Steel	SP0003SS

Technical Specification

Voltage rating 250Vac

Current rating 13A per outlet

Contact gap 3mm

No user serviceable parts

Back Boxes

Minimum recommended depth

	Flush	Dry lining
	35mm	35mm
1g	DB164	DB2540
2g	DB165	DB2541

Standards

BS 1363 Part 2

Terminal Capacity

	2.52	42	C2	10mm²
	2.5mm ²	4mm²	6mm²	10mm-
L&N	4	3	2	1